

श्री नं.१४ बाहिनी अड्डामा भएका मर्मत गर्नुपर्ने बिपद् व्यवस्थापन सामग्रीका लागि आवश्यक पर्ने पार्टसहरूको

स्पेसिफिकेशन

S.N.	Parts	Parameter	Technical Specification	Remarks
1	Chain Saw Chain for 40.64cm/16"	Pitch	3/8" Low Profile .325" 3/8" .404" 3/4"	
		Gauge	.043" (1.1mm), .050" (1.3mm), .058" (1.5mm) & .063" (1.6mm)	
		Cutter Type	Full chisel or semi chisel	
		Length	Chain rool (25 feet & 100 feet)	
		Angle of Chain	30 Degree	
		Diameter of Round File	5/32" (4.0 mm), 3/16" (4.8 mm) & 7/32" (5.5mm)	
		Standard	ISO or Equivalent	
2	Chain Saw Chain for 45cm/18"	Pitch	3/8" Low Profile .325" 3/8" .404" 3/4"	
		Gauge	.043" (1.1mm), .050" (1.3mm), .058" (1.5mm) & .063" (1.6mm)	
		Cutter Type	Full chisel or semi chisel	
		Length	Chain rool (25 feet & 100 feet)	
		Angle of Chain	30 Degree	
		Diameter of Round File	5/32" (4.0 mm), 3/16" (4.8 mm) & 7/32" (5.5mm)	
		Standard	ISO or Equivalent	
3	Chain Saw Chain for 50.8cm/20"	Pitch	3/8" Low Profile .325" 3/8" .404" 3/4"	
		Gauge	.043" (1.1mm), .050" (1.3mm), .058" (1.5mm) & .063" (1.6mm)	
		Cutter Type	Full chisel or semi chisel	
		Length	Chain rool (25 feet & 100 feet)	
		Angle of Chain	30 Degree	
		Diameter of Round File	5/32" (4.0 mm), 3/16" (4.8 mm) & 7/32" (5.5mm)	
		Standard	ISO or Equivalent	
4	Chain Saw Chain for 60.96cm/24"	Pitch	3/8" Low Profile .325" 3/8" .404" 3/4"	
		Gauge	.043" (1.1mm), .050" (1.3mm), .058" (1.5mm) & .063" (1.6mm)	
		Cutter Type	Full chisel or semi chisel	
		Length	Chain rool (25 feet & 100 feet)	
		Angle of Chain	30 Degree	
		Diameter of Round File	5/32" (4.0 mm), 3/16" (4.8 mm) & 7/32" (5.5mm)	
		Standard	ISO or Equivalent	
5	Demolition Hammer Bit	Material	40Cr Steel with Heat Treatment	
		Head Type	Flat	
		Length	16"	
		Diameter	1"	
		Shank	17mm Hex Shank (SDS Plus Shank, SDS Max, Shank, Pneumatic Collared Shank, PH65 Shank)	
		Standard	ISO or Equivalent	
6	Demolition Hammer Bit	Material	40Cr Steel with Heat Treatment	
		Head Type	Point	
		Length	16"	
		Diameter	1"	
		Shank	17mm Hex Shank (SDS Plus Shank, SDS Max, Shank, Pneumatic Collared Shank, PH65 Shank)	
		Standard	ISO or Equivalent	

S.N.	Parts	Parameter	Technical Specification	Remarks
7	Reciprocating saw blades for Metal	Material	High Carbon Steel	
		Teeth Per Inch	18	
		Length	9"	
		Thickness	0.042" (1mm)	
		Standard	ISO or Equivalent	
8	Reciprocating saw blades for Wood	Material	High Carbon Steel	
		Teeth Per Inch	5	
		Length	9"	
		Thickness	0.042" (1mm)	
		Standard	ISO or Equivalent	
9	Chain Saw Starter Rope	Material	Nylon/Polyester/Polypropylene /PP	
		Diameter	3.5mm	
		Length	3.5m	
		Standard	ISO or Equivalent	
10	Rotary Rescue Saw Bosch Concrete Diamond blade	Material	Inoxidable Metal/Acier in oxydable	
		Sinter	Laser/Sintering	
		Size	350 mm (14")*25.4mm (1")	
		Standard	ISO or Equivalent	
11	Rotary Rescue Saw Bosch Wood Diamond blade	Material	Inoxidable Metal/Acier in oxydable	
		Sinter	Laser/Sintering	
		Size	350 mm (14")*25.4mm (1")	
		Standard	ISO or Equivalent	
12	Heavy Duty Pavement Breaker Steel (Atlas Copco)	Size	14" UC Moil Point	
		Chisel Type	Moil Point	
		Standard	ISO or Equivalent	
13	Heavy Duty Pavement Breaker Steel (Atlas Copco)	Size	18" UC Moil Point	
		Chisel Type	Moil Point	
		Standard	ISO or Equivalent	
14	Heavy Duty Pavement Breaker Steel (Atlas Copco)	Size	24" UC Moil Point	
		Chisel Type	Moil Point	
		Standard	ISO or Equivalent	
15	Heavy Duty Pavement Breaker Steel (Atlas Copco)	Size	14"	
		Shank	Flate for 1" x 4-1/4" Shank	
		Chisel Type	Narrow Flate	
		Standard	ISO or Equivalent	
16	Heavy Duty Pavement Breaker Steel (Atlas Copco)	Size	18"	
		Shank	Flate for 1" x 4-1/4" Shank	
		Chisel Type	Narrow Flate	
		Standard	ISO or Equivalent	
17	Heavy Duty Pavement Breaker Steel (Atlas Copco)	Size	24"	
		Shank	Flate for 1" x 4-1/4" Shank	
		Chisel Type	Narrow Flate	
		Standard	ISO or Equivalent	