

Specification of Rice Steamer (100 Kg)

S.N.	Parameter	Specification	Remarks
1	Type	Electric Rice steamer with complete installation	
2	Function	Multifunction (Able to Steam Rice, Fish, Mutton, Chicken, Egg, Vegetables, Momo etc)	
3	Materials	Stainless Steel 304 grade or Better	
4	Insulation (all around)	Polyurethane foam or better	
5	Cooking Capacity	100 kg \pm 10% (Dry Rice)	
6	Features	Should have two fixed and two movable castor wheel for Movement	
		Should have insulation body	
		Should have push pull handles	
7	Steam Time	Maximum 60 Minutes (For Rice)	
8	Heat Preserving Time	Minimum 2.5 hours	
9	Door	Double	
10	Power	Maximum 25 KW	
11	Power Supply	Single/Three Phase; Minimum 3 meter Cable (Compatible with Nepal power supply)	
12	Trays Capacity	Minimum 20 Trays (Minimum 2mm thickness)	
13	Trays Properties	Scratch Resistance, Stainless Steel, Removable	
14	Accessories	Extra 7 Trays (4 with holes and 3 normal) should be provided	
15	Manuals	Operation Manual in English	
16	Warranty	Minimum 2 years from the date of installation or Provided by OEM whichever is greater	
17	Standard	ISO/CE or Equivalent	
18	Terms and Conditions	Installation including all necessary electrical accessories (MCB's, Switch Boards, Wires etc) will be the responsibility of the suppliers.	

Specification of Rice Steamer (60 Kg)

S.N.	Parameter	Specification	Remarks
1	Type	Electric Rice steamer with complete installation	
2	Function	Multifunction (Able to Steam Rice, Fish, Mutton, Chicken, Egg, Vegetables, Momo etc)	
3	Materials	Stainless Steel 304 grade or Better	
4	Insulation (all around)	Polyurethane foam or better	
5	Cooking Capacity	60 kg \pm 5% (Dry Rice)	
6	Features	Should have two fixed and two movable castor wheel for Movement	
		Should have insulation body	
		Should have push pull handles	
7	Steam Time	Maximum 60 Minutes (For Rice)	
8	Heat Preserving Time	Minimum 2.5 hours	
9	Door	Double	
10	Power	Maximum 25 KW	
11	Power Supply	Single/Three Phase; Minimum 3 meter Cable (Compatible with Nepal power supply)	

Handwritten signatures and initials are present at the bottom of the page, including a large signature on the left and several smaller initials and marks on the right.

12	Trays Capacity	Minimum 12 Trays (Minimum 2mm thickness)	
13	Trays Properties	Scratch Resistance, Stainless Steel, Removable	
14	Accessories	Extra 5 Trays (3 with holes and 2 normal) should be provided	
15	Manuals	Operation Manual in English	
16	Warranty	Minimum 2 years from the date of installation or Provided by OEM whichever is greater	
17	Standard	ISO/CE or Equivalent	
18	Terms and Conditions	Installation including all necessary electrical accessories (MCB's, Switch Boards, Wires etc) will be the responsibility of the suppliers.	