

**Specification of LED TV**

S.N	Parameter	Technical Specification	Remarks
1	Type	Smart, LED TV	
2	Screen Size	Minimum 43"	
3	Display Quality	Full HD	
4	Resolution	Minimum 1920 x 1080	
5	Refresh Rate	Min 60 Hz	
6	Connectivity	Minimum 2 x HDMI , 2 x USB, RF connection, Wifi	
7	Audio	Minimum 2 x 10W Speaker	
8	Accessories	Remote Control, TV Stand, Movable Wall Mount	
9	Standard	ISO or Equivalent	
10	Warranty	Minimum 1 year/ provided by OEM whichever is Greater	

**Specification of AC (1.5 Ton)**

S.N.	Parameters	Technical Specification	Remarks
1	AC Type	Inverter or Non Inverter	
		Split Type	
2	Cooling Capacity (BTU)	Minimum 18000	
3	Cooling EER (W/W)	Minimum 3	
4	Heating Capacity (BTU)	Minimum 18000	
5	Heating COP (W/W)	Minimum 3.2	
6	Refrigerant	R410A or Better	
7	Compressor Type	Rotary Type	
8	Power Supply	220V-240V/50HZ	
9	Operation Mode	4 Operation Mode (Heat, Cool, Dry, Auto)	
10	Cooling amp	7.2A-10A	
11	Fan Mode	3 Operation (High, Medium, Low)	
12	Indoor Noise Level (dBA)	Maximum 49	
13	Standard	ISO or Equivalent	
14	Warranty	Minimum 1 year/ Provided by OEM whichever is greater	

### Technical Specification of Generator 62.5KVA

S.N.	Parameters		Specifications	Remarks
1	Type		Diesel genset for continuous power supply running at ambient temp -5 deg celcius to 50 deg celcius	
2	Prime Power		62.5±2.5 KVA	
3	Dimension (LxBxH) in mm		Maximum 2450 x 1100 x 1550	
4	Power Factor		Minimum 0.8	
5	Rated Gen-set Output		230V/400V, 50Hz	
6	Engine	Type	Minimum 4 cylinder Diesel Engine	
		Cooling mode	Water Cooled	
7	Governer Type		Mechanical or Electronic	
8	Alternator	Type	A.C. Synchronous, self regulated	
		Voltage Regulation	≤ ±1%	
		Waveform Distortion	no load ≤2.5% ; Non-distorting balanced linear load ≤5%	
		Excitation	AVR, Brushless	
9	Insulation Class		H or better	
10	Protection Class		IP23 or equivalent	
11	Control panel	Type	Digital	
12	Canopy	Type	Enclosure must be modular sound attenuated, weather proof.	
			Door handle must be lockable type	
		Noise Level	Max 75 db @ 1 meter	
13	Continuous Operation		Minimum 8 hours	
14	features		Base integrated fuel tank	
			Anti-vibration pads should be fixed between engine and alternator.	
			Base Frame including position for forklift and lifting hook for crane to lift and move	
15	Quality Assurance		ISO certified or Equivalent	
16	Manufacture Year		2021 onwards	
17	Workshop Repair Manual And Operating Manual		Soft copy -1/1 set each.	
18	Spare Parts Catalogue		Soft copy -1/1 set	
19	Warranty		Minimum Two Years Global Warranty after delivery/Provided by OEM (which ever is greater)	
20	Final Delivery Requirement		Equipment operational demonstration and verification by the supplier during delivery of the equipment	



### Specification Teleprompter

S.N.	Parameter	Specification	Remarks
1	Reading Range	Minimum 6 m	
2	Monitor Size (Diagonal)	Minimum 17"	
3	Resolution	Minimum 1280 x 720	
4	Aspect Ratio	16:9	
5	Input	Minimum 1 x HDMI Minimum 1 x VGA	
6	Material of construction	Aluminum or better	
7	Beamsplitter Ratio	Minimum Transmission: 60% Maximum Reflectance: 40%	
8	Supported Operating Systems	Windows 10/ Mac	
9	Beamsplitter Material	Glass	
10	Mount Type	Mounting barcket must be included for tripod head	
11	Accessories to be included	Min 1 x Foot Control Pedal Min 1 x Hand Control Pedal Compatible teleprompter cover necessary cables (HDMI, VGA, Power Cable) Compatible Teleprompter driver software	
12	Standard	ISO or Equivalent	
13	Warranty	Min 1 year or Provided by OEM whichever is greater	