

Specification of 5.56 mm M16 Rifle Sling

S.N.	Parameters	Specification	Remarks
1	Material	95% Nylon minimum	
2	Pattern	Plain with weft rib	
3	Colour	Black	
4	Adjustable buckle	Material : Metal	
		Width : 30mm \pm 1mm	
		Length : 41mm \pm 1mm	
		Thickness : 2mm \pm 0.5mm	
5	D-ring	Material : Plastic	
		Width : 41mm \pm 1mm	
		Length : 35mm \pm 1mm	
		Thickness : 5mm \pm 1mm	
6	Tringular metal clip	Material : Metal	
		Thickness : 2.25 mm \pm 0.5 mm	
		Size : As per sample	
7	Sling tape size	1.80 meter length x width 3.3 cm \pm 2mm & thickness Min 2 mm (Main Sling)	
		55 cm length x width 2.5 cm \pm 1 mm & Thickness Min 1.3 mm (Top Sling Strap With D-ring)	
8	Featurers	2 x Plastic adjustable buckle with sling tape	
		1 x Plastic D-ring with sling tape	
		1 x Metal tringular clip	
		Sling tape should be strong & soft	
9	Product/Design	As per sample	

Specification of 5.56 mm Colt Commando Sling

S.N.	Parameters	Specification	Remarks
1	Material	95% Nylon minimum	
2	Pattern	Plain with weft rib	
3	Colour	Black	
4	Adjustable buckle	Material : Metal	
		Width : 30mm \pm 1mm	
		Length : 41mm \pm 1mm	
		Thickness : 2mm \pm 0.5mm	
5	Tringular metal clip	Material : Metal	
		Thickness : 2.25 mm \pm 0.5 mm	
		Size : As per sample	
6	Sling tape size	1.30 meter length x width 3.3 cm \pm 2mm & thickness Min 2 mm	
7	Featurers	2 x Plastic adjustable buckle with sling tape	
		1 x Metal tringular clip	
		Sling tape should be strong & soft	
8	Product/Design	As per sample	

A series of handwritten signatures and initials in black and green ink are located below the table. The signatures are somewhat stylized and overlapping. One signature in green is on the far right.