

Specification of Tyre & Battery

S.N.	Parameters	Specification		
	Tyre Sizes	Type	Load Index (minimum)	Speed Rating (minimum)
1	145/80 R 12	Tubed	70	T
2	100/90-17	Tubeless	50	P
3	115 R 15	Tubed	110	R
4	12.5R20	Tubed	90	H
5	14.00-20	Tubed	110	J
6	155-70R13	Tubeless	75	T
7	16/17-20	Offroad tyre	100	L
8	17.5-00-25	Offroad tyre	100	L
9	185/65 R 14	Tubeless	86	T
10	195 R15	Tubeless	104	Q
11	2.75-17	Tubeless	40	P
12	2.75-18	Tubeless	40	P
13	20.5-00-25	Offroad tyre	100	L
14	205/75 R 14	Tubeless	90	S
15	205/75 R 16	Tubeless	100	L
16	205/75 R-17.5	Tubed	118	L
17	205/80 R 16	Tubeless	108	R
18	205/80R 17.5	Tubed	118	L
19	215/ R-15	Tubeless	100	T
20	215/55 R-16	Tubeless	90	V
21	215/60 R-16	Tubeless	100	L
22	215/70R-16	Tubeless	100	T
23	215/80 R-16	Tubeless	100	S
24	225/100R16	Tubed	90	H
25	225/70 R 15	Tubeless	110	R
26	23.5-00-25	Offroad tyre	100	L
27	235/80 R-15	Tubeless	110	N
28	245/45 R 17	Tubeless	110	S
29	265/60 R18	Tubeless	110	H
30	265/75 R 16	Tubeless	110	U
31	265/80 R-16	Tubeless	110	Q
32	275/70 R 16	Tubeless	110	U
33	275/75 R18	Tubeless	110	U
34	275/80 R16	Tubeless	110	U
35	3.00-17	Tubeless	50	P
36	3.00-18	Tubeless	50	P
37	6.50-15	Tubeless	70	Q
38	6.50-16	Tubeless	70	Q
39	7.00 R 16	Tubed	110	K
40	8.00-19	Tubed	70	L
41	8.25-00-20	Tubed	85	L
42	8.25-16	Tubed	70	L

S.N.	Parameters	Specification		
	Tyre Sizes	Type	Load Index (minimum)	Speed Rating (minimum)
43	8.25-19	Tubed	70	L
44	80/100 - 17	Tubeless	45	P
45	9.00-20	Tubed	110	J
46	90/90 -17	Tubeless	55	P

Terms and Conditions

47	Features	Should have same tread pattern for same size of tyre
48	Accessories	Flaps, tube and valve should be provided as per requirement of tyres.
49	Manufacturing Date	Not before 6 months on the day of Delivery.
50	Standard	ISO or Equivalent
51	Warranty	1. For Vechile Tyers Minimum 50,000 KMs 2. For Motercycle tyre Minimum 15000 KM

S.N.	Parameters	Specification
------	------------	---------------

Battery

1	12 V 65 AH	Lead Acid, Sealed Maintenance Free (SMF). Terminals: As per requirement. Serial number /Manufacturing date should be clearly stated in the battery.
2	12V 5 AH	
3	12 V 110AH	
4	12 V 2.5 AH	
5	12 V 7 AH	

Terms and Conditions

6	Manufacturing Date	Not before 6 months on the day of Delivery.
7	Standard	ISO or Equivalent
8	Warranty	Minimum 2 years